

Logic Programming (PLP 11.3)

Predicate Calculus
Clocksin-Mellish Procedure
Horn Clauses

Carlos Varela
Rensselaer Polytechnic Institute

August 30, 2007

C. Varela

1

Propositional Logic

- Assigning truth values to logical propositions.
- Formula syntax:

f	$::=$	v	symbol
		$f \wedge f$	and
		$f \vee f$	or
		$f \Leftrightarrow f$	if and only if
		$f \Rightarrow f$	implies
		$\neg f$	not

C. Varela

2

Truth Values

- To assign a truth values to a propositional formula, we have to assign truth values to each of its atoms (symbols).
- Formula semantics:

a	b	$a \wedge b$	$a \vee b$	$a \Leftrightarrow b$	$a \Rightarrow b$	$\neg a$
False	False	F	F	T	T	T
False	True	F	T	F	T	T
True	False	F	T	F	F	F
True	True	T	T	T	T	F

C. Varela

3

Tautologies

- A *tautology* is a formula, **true** for all possible assignments.

- For example: $\neg\neg p \Leftrightarrow p$

- The contrapositive law:

$$(p \Rightarrow q) \Leftrightarrow (\neg q \Rightarrow \neg p)$$

- De Morgan's law:

$$\neg(p \wedge q) \Leftrightarrow (\neg p \vee \neg q)$$

C. Varela

4

First Order Predicate Calculus

- Adds variables, terms, and (first-order) quantification of variables.
- Predicate syntax:

a	$::=$	$p(v_1, v_2, \dots, v_n)$	predicate
f	$::=$	a	atom
		$v = p(v_1, v_2, \dots, v_n)$	equality
		$v_1 = v_2$	
		$f \wedge f$ $f \vee f$ $f \Leftrightarrow f$ $f \Rightarrow f$ $\neg f$	
		$\forall v. f$	universal quantifier
		$\exists v. f$	existential quantifier


C. Varela

5

Predicate Calculus

- In mathematical logic, a *predicate* is a function that maps constants or variables to **true** and **false**.
- Predicate calculus enables reasoning about propositions.

- For example:



C. Varela

6

Quantifiers

- **Universal (\forall)** quantifier indicates that the proposition is true for **all** variable values.
- **Existential (\exists)** quantifier indicates that the proposition is true for **at least one** value of the variable.
- For example:

$$\forall A \forall B [\exists C [\text{takes}(A,C) \wedge \text{takes}(B,C)] \Rightarrow \text{classmates}(A,B)]$$

C. Varela

7

Structural Congruence Laws

$$P_1 \Rightarrow P_2 = \neg P_1 \vee P_2$$

$$\neg \exists X [P(X)] = \forall X [\neg P(X)]$$

$$\neg \forall X [P(X)] = \exists X [\neg P(X)]$$

$$\neg (P_1 \wedge P_2) = \neg P_1 \vee \neg P_2$$

$$\neg (P_1 \vee P_2) = \neg P_1 \wedge \neg P_2$$

$$\neg \neg P = P$$

$$(P_1 \Leftrightarrow P_2) = (P_1 \Rightarrow P_2) \wedge (P_2 \Rightarrow P_1)$$

$$P_1 \vee (P_2 \wedge P_3) = (P_1 \vee P_2) \wedge (P_1 \vee P_3)$$

$$P_1 \wedge (P_2 \vee P_3) = (P_1 \wedge P_2) \vee (P_1 \wedge P_3)$$

$$P_1 \vee P_2 = P_2 \vee P_1$$

C. Varela

8

Clausal Form

- Looking for a *minimal kernel* appropriate for theorem proving.
- Propositions are transformed into **normal form** by using structural congruence relationship.
- One popular normal form candidate is *clausal form*.
- Clocksin and Melish (1994) introduce a 5-step procedure to convert first-order logic propositions into clausal form.

C. Varela

9

Clocksin and Melish Procedure

1. Eliminate implication (\Rightarrow) and equivalence (\Leftrightarrow).
2. Move negation (\neg) inwards to individual terms.
3. *Skolemization*: eliminate existential quantifiers (\exists).
4. Move universal quantifiers (\forall) to top-level and make implicit, i.e., all variables are universally quantified.
5. Use distributive, associative and commutative rules of \vee , \wedge , and \neg , to move into *conjunctive normal form*, i.e., a conjunction of disjunctions (or *clauses*).

C. Varela

10

Example

$$\forall A [\neg \text{student}(A) \Rightarrow (\neg \text{dorm_resident}(A) \wedge \neg \exists B [\text{takes}(A,B) \wedge \text{class}(B)])]$$

1. Eliminate implication (\Rightarrow) and equivalence (\Leftrightarrow).

$$\forall A [\text{student}(A) \vee (\neg \text{dorm_resident}(A) \wedge \neg \exists B [\text{takes}(A,B) \wedge \text{class}(B)])]$$

2. Move negation (\neg) inwards to individual terms.

$$\forall A [\text{student}(A) \vee (\neg \text{dorm_resident}(A) \wedge \forall B [\neg (\text{takes}(A,B) \wedge \text{class}(B))])]$$

$$\forall A [\text{student}(A) \vee (\neg \text{dorm_resident}(A) \wedge \forall B [\neg \text{takes}(A,B) \vee \neg \text{class}(B)])]$$

C. Varela

11

Example Continued

$$\forall A [\text{student}(A) \vee (\neg \text{dorm_resident}(A) \wedge \forall B [\neg \text{takes}(A,B) \vee \neg \text{class}(B)])]$$

3. *Skolemization*: eliminate existential quantifiers (\exists).
4. Move universal quantifiers (\forall) to top-level and make implicit, i.e., all variables are universally quantified.

$$\text{student}(A) \vee (\neg \text{dorm_resident}(A) \wedge (\neg \text{takes}(A,B) \vee \neg \text{class}(B)))$$

5. Use distributive, associative and commutative rules of \vee , \wedge , and \neg , to move into *conjunctive normal form*, i.e., a conjunction of disjunctions (or *clauses*).

$$(\text{student}(A) \vee \neg \text{dorm_resident}(A)) \wedge (\text{student}(A) \vee \neg \text{takes}(A,B) \vee \neg \text{class}(B))$$

C. Varela

12

Clausal Form to Prolog

```
(student(A) ∨ ¬dorm_resident(A)) ∧  
(student(A) ∨ ¬takes(A,B) ∨ ¬class(B))
```

6. Use commutativity of \vee to move negated terms to the right of each clause.

7. Use $P_1 \vee \neg P_2 \equiv P_2 \Rightarrow P_1 \equiv P_1 \Leftarrow P_2$

```
(student(A) ⇐ dorm_resident(A)) ∧  
(student(A) ⇐ ¬(¬takes(A,B) ∨ ¬class(B)))
```

8. Move Horn clauses to Prolog:

```
student(A) :- dorm_resident(A).  
student(A) :- takes(A,B), class(B).
```

C. Varela

13

Skolemization

```
∃X [takes(X,cs101) ∧ class_year(X,2)]
```

introduce a Skolem constant to get rid of existential quantifier (\exists):

```
takes(x,cs101) ∧ class_year(x,2)
```

```
∀X [¬dorm_resident(X) ∨  
∃A [campus_address_of(X,A)]]
```

introduce a Skolem function to get rid of existential quantifier (\exists):

```
∀X [¬dorm_resident(X) ∨  
campus_address_of(X,f(X))]
```

C. Varela

14

Limitations

- If more than one non-negated (positive) term in a clause, then it cannot be moved to a Horn clause (which restricts clauses to only one head term).
- If zero non-negated (positive) terms, the same problem arises (Prolog's inability to prove logical negations).
- For example:
 - « every living thing is an animal or a plant »

```
animal(X) ∨ plant(X) ∨ ¬living(X)  
animal(X) ∨ plant(X) ⇐ living(X)
```

C. Varela

15

Exercises

4. What is the logical meaning of the second Skolemization example if we do not introduce a Skolem function?
5. Convert the following predicates into Conjunctive Normal Form, and if possible, into Horn clauses:
 - a) $\forall C [\text{rainy}(C) \wedge \text{cold}(C) \Rightarrow \text{snowy}(C)]$
 - b) $\exists C [\neg \text{snowy}(C)]$
 - c) $\neg \exists C [\text{snowy}(C)]$
6. PLP Exercise 11.21 (pg 654).
7. *PLP Exercise 11.23 (pg 654).

C. Varela

16