

Declarative Computation Model

Memory management (VRH 2.5)

Carlos Varela
RPI
October 30, 2009

Adapted with permission from:
Seif Haridi
KTH
Peter Van Roy
UCL

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

1

Memory Management

- Semantic stack and store sizes during computation
 - analysis using operational semantics
 - recursion used for looping
 - efficient because of last call optimization
 - memory life cycle
 - garbage collection

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

2

Last call optimization

- Consider the following procedure

```
proc {Loop10 I}
  if I == 10 then skip
  else
    {Browse I}
    {Loop10 I+1}
  end
end
```

Recursive call
is the last call

- This procedure does **not** increase the size of the STACK
- It behaves like a looping construct

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

3

Last call optimization

```
proc {Loop10 I}
  if I == 10 then skip
  else
    {Browse I}
    {Loop10 I+1}
  end
end
```

ST: [({Loop10 0}, E₀)]

ST: [({Browse I}, {I → i₀, ...})
({Loop10 I+1}, {I → i₀, ...})]
σ : { i₀ = 0, ... }

ST: [({Loop10 I+1}, {I → i₀, ...})]
σ : { i₀ = 0, ... }

ST: [({Browse I}, {I → i₁, ...})
({Loop10 I+1}, {I → i₁, ...})]
σ : { i₀ = 0, i₁ = 1, ... }

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

4

Stack and Store Size

```
proc {Loop10 I}
  if I == 10 then skip
  else
    {Browse I}
    {Loop10 I+1}
  end
end
```

ST: [({Browse I}, {I → i_k, ...})
({Loop10 I+1}, {I → i_k, ...})]
σ : { i₀ = 0, i₁ = 1, ..., i_{k-1} = k-1, i_k = k, ... }

The semantic stack size is bounded by a constant.
But the store size keeps increasing with the computation.

Notice that at (k+1)th recursive call, we only need i_k
If we can keep the store size constant, we can run indefinitely
with a constant memory size.

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

5

Garbage collection

```
proc {Loop10 I}
  if I == 10 then skip
  else
    {Browse I}
    {Loop10 I+1}
  end
end
```

ST: [({Browse I}, {I → i_k, ...})
({Loop10 I+1}, {I → i_k, ...})]
σ : { i₀ = 0, i₁ = 1, ..., i_{k-1} = k-1, i_k = k, ... }

Garbage collection is an algorithm (a task) that removes from
memory (store) all cells that are not accessible from the stack


ST: [({Browse I}, {I → i_k, ...})
({Loop10 I+1}, {I → i_k, ...})]
σ : { i_k = k, ... }

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

6

The memory life cycle

- **Active memory** is what the program needs to continue execution (semantic stack + reachable part of store)
- Memory that is no longer needed is of two kinds:
 - Can be immediately deallocated (i.e., semantic stack)
 - Simply becomes **inactive** (i.e., store)
- Reclaiming inactive memory is the hardest part of memory management
 - **Garbage collection** is automatic reclaiming



C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

7

Garbage Collection

- Lower-level languages (C, C++) do not have automatic garbage collection.
- Manual memory management can be more efficient but it is also more error-prone, e.g.:
 - Dangling references
 - Reclaiming reachable memory blocks
 - Memory leaks
 - Not reclaiming unreachable memory blocks
- Higher-level languages (Erlang, Java, Lisp, Smalltalk) typically have automatic garbage collection.
- Modern algorithms are efficient enough---minimal memory and time penalties.

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

8

Garbage Collection Algorithms

- Reference Counting algorithms
 - Keep track of number of references to memory blocks
 - When count is 0, memory block is reclaimed.
 - Cannot collect cycles of garbage.
- Mark-and-Sweep algorithms
 - Phase 1: Determine active memory
 - Following *pointers* (in Oz, referenced store variables) from a *root set* (in Oz, the semantic stack).
 - Phase 2: Compact memory in one contiguous region.
 - Everything outside this region is free.
 - Generally must briefly pause the application memory mutation while collecting.

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

9

Avoiding memory leaks

- Consider the following function

```

fun {Sum X L1 L}
  case L1 of Y|L2 then {Sum X+Y L2 L}
  else X end
end
  
```

```

L= [1 2 3 ... 1000000]
{Sum 0 L}
  
```

- Since it keeps a pointer to the original list L, L will stay in memory during the whole execution of Sum.

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

10

Avoiding memory leaks

- Consider the following function

```

fun {Sum X L1}
  case L1 of Y|L2 then {Sum X+Y L2}
  else X end
end
  
```

```

L= [1 2 3 ... 1000000]
{Sum 0 L}
  
```

- Here, the reference to L is lost immediately and its space can be collected as the function executes.

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

11

Managing external references

- External resources are data structures outside the current O.S. process.
- There can be pointers from internal data structures to external resources, e.g.
 - An open file in a file system
 - A graphic entity in a graphics display
 - If the internal data structure is reclaimed, then the external resource needs to be cleaned up (e.g., remove graphical entity, close file)
- There can be pointers from external resources to internal data structures, e.g.
 - A database server
 - A web service
 - If the internal data structure is reachable from the outside, it should not be reclaimed.

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

12

Local Mozart Garbage Collector

- Copying dual-space algorithm
- Advantage : Execution time is proportional to the active memory size, not total memory size.
- Disadvantage : Half of the total memory is unusable at any given time

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

13

Exercises

59. What do you expect to happen if you try to execute the following statement?
Try to answer without actually executing it!

```
local T = tree(key:A left:B right:C value:D) in  
  A = 1  
  B = 2  
  C = 3  
  D = 4  
end
```

60. VRH Exercise 2.9.9 (page 109).
61. Any realistic computer system has a memory cache for fast access to frequently used data. Can you think of any issues with garbage collection in a system that has a memory cache?

C. Varela; Adapted w/permission from S. Haridi and P. Van Roy

14