Logic Programming (PLP 11)
Predicate Calculus, Horn Clauses, Clocksin-Mellish Procedure

Carlos Varela
Rensselaer Polytechnic Institute

November 6, 2026

An Early (1971) "Conversation"

USER:

Cats kill mice.

Tom is a cat who does not like mice who eat cheese.

Jerry is a mouse who eats cheese.

Max is not a mouse.

What does Tom do?

COMPUTER:

Tom does not like mice who eat cheese.

Tom kills mice.

USER:

Who is a cat?

COMPUTER:

Tom.

USER:

What does Jerry eat?

COMPUTER:

Cheese.

USER:

Who does not like mice who eat cheese?

COMPUTER:

Tom.

USER:

What does Tom eat?

COMPUTER:

What cats who do not like mice who eat cheese eat.

Another Conversation

USER:

Every psychiatrist is a person.
Every person he analyzes is sick.
Jacques is a psychiatrist in Marseille.
Is Jacques a person?
Where is Jacques?
Is Jacques sick?

COMPUTER:

Yes.
In Marseille.
I don't know.

Logic programming

- A program is a collection of *axioms*, from which theorems can be proven.
- A *goal* states the theorem to be proved.
- A logic programming language implementation attempts to satisfy the goal given the axioms and built-in inference mechanism.

Propositional Logic

- Assigning truth values to logical propositions.
- Formula syntax:

f	::=	v	symbol
	|	f ∧ f	and
	|	f ∨ f	or
	|	f ⇔ f	if and only if
	|	f ⇒ f	implies
	|	¬f	not

Truth Values

- To assign a truth value to a propositional formula, we have to assign truth values to each of its atoms (symbols).
- Formula semantics:

a	b	$a \wedge b$	$a \vee b$	$a \Leftrightarrow b$	$a \Rightarrow b$	$\neg a$
False	False	F	F	T	T	T
False	True	F	T	F	T	T
True	False	F	T	F	F	F
True	True	T	T	T	T	F

Tautologies

- A *tautology* is a formula, true for all possible assignments.
- For example: $p \vee \neg p$ (The law of the excluded middle)

  $\neg\neg p \Leftrightarrow p$
- The contrapositive law:

  $(p \Rightarrow q) \Leftrightarrow (\neg q \Rightarrow \neg p)$
- De Morgan's law:

  $\neg(p \wedge q) \Leftrightarrow (\neg p \vee \neg q)$

First Order Predicate Calculus

- Adds variables, terms, and (first-order) quantification of variables.
- Predicate syntax:

a	::=	$p(v_1, v_2, \ldots, v_n)$	predicate
f	::=	a	atom
	|	$v = p(v_1, v_2, \ldots, v_n)$	equality
	|	$v_1 = v_2$	
	|	$f \wedge f \mid f \vee f \mid f \Leftrightarrow f \mid f \Rightarrow f \mid \neg f$	
	|	$\forall v[f]$	universal quantifier
	|	$\exists v[f]$	existential quantifier

Predicate Calculus

- In mathematical logic, a *predicate* is a function that maps constants or variables to true and false.
- Predicate calculus enables reasoning about propositions.

- For example:

$$\forall C\ [rainy(C) \wedge cold(C) \Rightarrow snowy(C)]$$

Quantifier
($\forall$, $\exists$)

Operators
($\wedge$,$\vee$,$\Leftrightarrow$,$\Rightarrow$,$\neg$)

Quantifiers

- *Universal* (∀) quantifier indicates that the proposition is true for **all** variable values.
- *Existential* (∃) quantifier indicates that the proposition is true for **at least one** value of the variable.
- For example:

```
∀A[∀B[∃C[takes(A,C) ∧ takes(B,C)] ⇒ classmates(A,B)]]
```

Structural Congruence Laws

$$P_1 \Rightarrow P_2 \equiv \neg P_1 \vee P_2$$

$$\neg\exists X\ [P(X)] \equiv \forall X\ [\neg P(X)]$$
$$\neg\forall X\ [P(X)] \equiv \exists X\ [\neg P(X)]$$

$$\neg(P_1 \wedge P_2) \equiv \neg P_1 \vee \neg P_2$$
$$\neg(P_1 \vee P_2) \equiv \neg P_1 \wedge \neg P_2$$
$$\neg\neg P \equiv P$$

$$(P_1 \Leftrightarrow P_2) \equiv (P_1 \Rightarrow P_2) \wedge (P_2 \Rightarrow P_1)$$

$$P_1 \vee (P_2 \wedge P_3) \equiv (P_1 \vee P_2) \wedge (P_1 \vee P_3)$$
$$P_1 \wedge (P_2 \vee P_3) \equiv (P_1 \wedge P_2) \vee (P_1 \wedge P_3)$$

$$P_1 \vee P_2 \equiv P_2 \vee P_1$$

Clausal Form

- Looking for a *minimal kernel* appropriate for theorem proving.
- Propositions are transformed into normal form by using structural congruence relationship.
- One popular normal form candidate is *clausal form*.
- Clocksin and Melish (1994) introduce a 5-step procedure to convert first-order logic propositions into clausal form.

Clocksin and Melish Procedure

1. Eliminate implication ($\Rightarrow$) and equivalence ($\Leftrightarrow$).
2. Move negation ($\neg$) inwards to individual terms.
3. *Skolemization*: eliminate existential quantifiers ($\exists$).
4. Move universal quantifiers ($\forall$) to top-level and make implicit , i.e., all variables are universally quantified.
5. Use distributive, associative and commutative rules of $\vee$, $\wedge$, and $\neg$, to move into *conjuctive normal form*, i.e., a conjuction of disjunctions (or *clauses*.)

Example

$$\forall A\ [\neg student(A) \Rightarrow (\neg dorm_resident(A) \wedge \neg\exists B\ [takes(A,B) \wedge class(B)])]$$

1. Eliminate implication ($\Rightarrow$) and equivalence ($\Leftrightarrow$).

$$\forall A\ [student(A) \vee (\neg dorm_resident(A) \wedge \neg\exists B\ [takes(A,B) \wedge class(B)])]$$

2. Move negation ($\neg$) inwards to individual terms.

$$\forall A\ [student(A) \vee (\neg dorm_resident(A) \wedge \forall B\ [\neg(takes(A,B) \wedge class(B))])]$$

$$\forall A\ [student(A) \vee (\neg dorm_resident(A) \wedge \forall B\ [\neg takes(A,B) \vee \neg class(B)])]$$

Example Continued

```
∀A [student(A) ∨ (¬dorm_resident(A) ∧
                  ∀B [¬takes(A,B) ∨ ¬class(B)])]
```

3. *Skolemization*: eliminate existential quantifiers (∃).
4. Move universal quantifiers (∀) to top-level and make implicit , i.e., all variables are universally quantified.

```
student(A) ∨ (¬dorm_resident(A) ∧
              (¬takes(A,B) ∨ ¬class(B)))
```

5. Use distributive, associative and commutative rules of ∨, ∧, and ¬, to move into *conjuctive normal form*, i.e., a conjuction of disjunctions (or *clauses*.)

```
(student(A) ∨ ¬dorm_resident(A)) ∧
(student(A) ∨ ¬takes(A,B) ∨ ¬class(B))
```

Horn clauses

- A standard form for writing axioms, e.g.:

```
father(X,Y) ⇐ parent(X,Y), male(X).
```

- The Horn clause consists of:
  - A *head* or consequent term H, and
  - A *body* consisting of terms B_i

$$H \Leftarrow B_0 , B_1 , \ldots, B_n$$

- The semantics is:

« If B_0 , B_1 , …, and B_n, then H »

Clausal Form to Prolog

```
(student(A) ∨ ¬dorm_resident(A)) ∧
(student(A) ∨ ¬takes(A,B) ∨ ¬class(B))
```

6. Use commutativity of $\vee$ to move negated terms to the right of each clause.
7. Use $P_1 \vee \neg P_2 \equiv P_2 \Rightarrow P_1 \equiv P_1 \Leftarrow P_2$

```
(student(A) ⇐ dorm_resident(A)) ∧
(student(A) ⇐ ¬(¬takes(A,B) ∨ ¬class(B)))
```

8. Move Horn clauses to Prolog:

```
student(A) :- dorm_resident(A).
student(A) :- takes(A,B),class(B).
```

Skolemization

```
∃X [takes(X,cs101) ∧ class_year(X,2)]
```

introduce a Skolem constant to get rid of existential quantifier (∃):

```
takes(x,cs101) ∧ class_year(x,2)
```

```
∀X [¬dorm_resident(X) ∨
     ∃A [campus_address_of(X,A)]]
```

introduce a Skolem function to get rid of existential quantifier (∃):

```
∀X [¬dorm_resident(X) ∨
     campus_address_of(X,f(X)]
```

Limitations

- If more than one non-negated (positive) term in a clause, then it cannot be moved to a Horn clause (which restricts clauses to only one head term).

- If zero non-negated (positive) terms, the same problem arises (Prolog's inability to prove logical negations).

- For example:
  - « every living thing is an animal or a plant »

```
animal(X) ∨ plant(X) ∨ ¬living(X)
animal(X) ∨ plant(X) ⇐ living(X)
```

Exercises

67. What is the logical meaning of the second Skolemization example if we do not introduce a Skolem function?
68. Convert the following predicates into Conjunctive Normal Form, and if possible, into Horn clauses:
    a) $\forall C\ [rainy(C) \wedge cold(C) \Rightarrow snowy(C)]$
    b) $\exists C\ [\neg snowy(C)]$
    c) $\neg\exists C\ [snowy(C)]$
69. PLP Exercise 11.5 (pg 571).
70. PLP Exercise 11.6 (pg 571).